



# Mieux Indoor LED Video Wall

## Features

<p><b>Free &amp; Seamless Splicing</b></p>	<p><b>Ultrahigh Refresh Rate</b></p>	<p><b>Wide Viewing Angle</b></p>
<p><b>High Brightness</b></p>	<p><b>Quick Response Time</b></p>	<p><b>Less Occupation of Space</b></p>
<p><b>More Color Depth</b></p>	<p><b>Wide Color Gamut</b></p>	<p><b>Superior Contrast Ratio</b></p>
<p><b>Greater Uniformity</b></p>	<p><b>SMD 3in1 Technology</b></p>	<p><b>Excellent Heat Dissipation</b></p>



Specifications		
<b>Physical Parameter</b>	Pixel Pitch	2.5
	LED Type	SMD 3-in-1 LED Type
	Pixel Density (pixels/m <sup>2</sup> )	4,22,500 Dots
	Resolution of LED Module (W*H )	208*104
	Resolution of Cabinet (W* H)	416*312
	LED Module Size (W* H)	320*160 mm
	Cabinet Size (W* H* D)	640*480*55 mm
	No. of Modules Per Cabinet (W* H)	2*3
	Module Connection	Ribbon Cable
	Cabinet Area	0.3072 m <sup>2</sup>
	Cabinet Material	Die-Cast Aluminium / MS
<b>Optical Parameter</b>	Brightness - Adjustable	600 nits
	Contrast Ratio	7000 : 1
	Horizontal Viewing Angle	160°
	Vertical Viewing Angle	160°
	Color Temperature - Default	6500K ± 200 K
	Color Temperature - Adjustable	3200~9300 K
<b>Electrical Parameter</b>	Average Power Consumption	≤150 W/ m <sup>2</sup>
	Max Power Consumption	≤650 W/ m <sup>2</sup>
	Input Power Voltage	100-240VAC, 50/60 (Hz)
<b>Processing Parameter</b>	Drive Mode	Constant Current Drive
	Frame Rate	30-120 Hz
	Refresh Rate	1920-3840 Hz
	Gray Scale Processing	14-18 bit
<b>Operation Conditions</b>	Operating Temp/Humidity	-10 - 45 °C/ 10% - 90%RH
	Storage Temp/Humidity	-20 - 60 °C/ 10% - 90%RH
	IP Rating	IP43
	Life span, typ.	100,000 Hrs
<b>Service</b>	Front	
<b>Application</b>	Indoor	

\*Remark: Due to continuous product development, the specifications & product image may change without prior intimation.



## Mieux Display Private Limited

